



Packaging Machinery & Systems
made for you



Semiautomatic pallet wrapper
with rotary arm

700

STANDARD MACHINE TECHNICAL CHARACTERISTICS

- Production of up to **20 pallets/hour**, depending on the operator and the characteristics of the load.
- Powered film carriage in the rotary arm with frequency inverter.
- **Powered pre-stretch 300%**
- Automatic load height detection by photocell.
- Soft start/stop with stop in position and **SCHNEIDER** frequency inverter.
- 4 wrapping cycles: simple / double/ double-plus / complete.
- Wrapping cycles counter.
- Top and bottom reinforcement wraps independently adjustable.
- Controlled by **SIEMENS PLC** with LCD touch screen.
- Ergonomic control panel.



Powered pre-stretch 300%



Obstacles detection by photocell.



Special options



- Black loads detection by ultrasounds
- Stainless steel 304
- Explosive atmospheres ATEX
- Sub-zero temperatures down to -30°C
- Special heights
- Different pre-stretch ratios 150%, 200%, 300% o 400%
- Safety fences and muting barriers.
- *COMPLETE CUSTOMIZATION*



Photo: Stainless steel model 700



Technical features	Standard
Maximum height	2.300 mm (other heights on request)
Maximum dimensions of the pallet and load	Up to 1.200 x 1.100 mm
Electrical power	220 - 240 V 50 / 60 Hz
Installed power	1.25 Kw
Film carriage	Pre-stretch 300%
Stop in position	Standard
Progressive start/stop with frequency inverter	Standard
Load detection by photocell	Standard
PLC with touch screen	Standard

Standard machine layout

